

TXE1eco

THE ROBUST AND RELIABLE BASIC PUMP

The TXE1eco is equipped with a powerful electric motor and can be effortlessly connected to large tension cylinders thanks to the 7-litre tank. It offers a maximum operating pressure of 1,500 bar and a flow rate of up to 3 litres/min. The pump has an integrated pressure gauge for easy reading of the pressure.

This power pack can be operated by remote control and is perfect for applications where no documentation is required.



PRESSURE GAUGE

Pressure gauge integrated into the pump for easy pressure control



7L OIL VOLUME

For large or several simultaneously connected tools



OPERATION

Via wired remote control



MODELS // DATA

Typ Type	Betriebsart Operation mode	max. Betriebsdruck Pressure max.		Volumenstrom bei 0 - 120 bar Flow rate at xxx - xxxx psi		Volumenstrom bei 120 - 1.500 bar Flow rate at xxx - xxxx psi		Motorleistung Motor power		Spannungsvarianten Voltage versions	Maße (L1 x B1 x H1) Dimensions (L1 x B1 x H1)	Gewicht* Weight*	
		bar	psi	l/min	gal/min	l/min	gal/min	kW	hp			kg	lbs
TXE1eco	elektrisch + manuell electric +manual	1.500	21,756	1,2	0,32	0,35	0,09	1,1	1,48	230V 50/60Hz	380 x 630 x 360 mm	38	84
										110V 50/60Hz			
										400V 50H			

Repeat accuracy: ≤ 4%, depending on the bolted joint. Technical data without guarantee.